

Sockets (ATHS) • Hex Keys

Sockets (ATHS)

Anti-FOD Sockets are manufactured to fit conventional square drives. They feature a generous through-hole to enable the use of hex keys when necessary for Hi-Lok®, Hi-Lite®, and Hi-Tigue® installations. A set screw is provided to positively retain the sockets onto the square drives as an anti-FOD measure.



ATHS437



Anti-Fod Hex Sockets

Socket (ATHS) Measurements

PART NUMBER	HEX OPENING (6-POINT)	SQUARE DRIVE-SIZE	NOSE DIAMETER	OVERALL LENGTH
ATHS156	5/32	1/4	0.280	0.86
ATHS187	3/16	1/4	0.312	0.86
ATHS218	7/32	1/4	0.312	0.86
ATHS250	1/4	1/4	0.375	0.88
ATHS281	9/32	1/4	0.410	0.88
ATHS312	5/16	1/4	0.467	0.88
ATHS343	11/32	1/4	0.508	0.88
ATHS375	3/8	3/8	0.560	1.00
ATHS375A	3/8	1/4	0.560	0.88
ATHS437	7/16	3/8	0.640	1.00
ATHS437A	7/16	1/4	0.600	0.86
ATHS500	1/2	3/8	0.710	1.00

Hex Keys

Hex keys for hand-tool applications, and replacement tips for most popular air-tool systems.

Hex Keys and Replacement Tips

Hand-Held Hex Keys			Replacement Tips			
HEX KEY SIZE	PLASTIC HANDLE	T-HANDLE	HI-SHEAR® STANDARD	HI-SHEAR® SUPER KEY	VOI-SHAN KWIK-KEY®	LOK-FAST QRS®
1/16 (0.062)	ATHK062		HLT140-062	HLT140K062	KK101-06	QRK5
5/64 (0.079)	ATHK079		HLT140-078	HLT140K078	KK101-07	QRK6
3/32 (0.094)	ATHK094	ATHK094T	HLT140-094	HLT140K094	KK101-09	QRK8
1/8 (0.125)	ATHK125	ATHK125T	HLT140-125	HLT140K125		QRK10
5/32 (0.156)		ATHK156T	HLT140-156	HLT140K156		QRK12
3/16 (0.187)		ATHK187T	HLT140-187	HLT140K187		
7/32 (0.218)		ATHK218T				
1/4 (0.250)		ATHK250T				



Through Hole Extensions

Available in 2" and 4" lengths

